



AUTOGUARD™ 50/50 ANTIFREEZE & COOLANT

AUTOGUARD 50/50 Antifreeze & Coolant is an ethylene glycol base coolant for both automotive aluminum block engines and low silicate heavy duty diesel engines. When used in heavy-duty applications, the addition of separate Supplement Coolant Additives (SCAs) is required.

AUTOGUARD 50/50 Antifreeze & Coolant Protects all cooling system parts including aluminum and modern high lead solders. It has a service life of 2-years from date put in service.

AUTOGUARD 50/50 Antifreeze & Coolant prevents freezing, boil-over, rusting, corrosion, sludge clogging and scale build-up throughout the cooling system.

AUTOGUARD 50/50 Antifreeze & Coolant meets or exceeds the following specifications:

ASTM D-3306	SAE J1034	Mack Truck
ASTM D-4340	Caterpillar	TMC RP 302B
Chrysler MS 7170	Cummins 90T8-4	SAE J1941
Ford ESE-M97B44-A	G.M. 1899M	ASTM D-4985
G.M. 1825M	John Deere H24B1/C1	Volvo/G.M. Heavy Truck

AUTOGUARD 50/50 Antifreeze & Coolant is pre-diluted and ready to use.
DO NOT DILUTE.



Warren Oil Company, Inc

Dunn, NC 28334; Benton, AL 36758; San Antonio, TX 78210;
Marion, IL 62959; Johnstown, PA 15909; West Memphis, AR 72301



AUTOGUARD™ 50/50 ANTIFREEZE & COOLANT

Typical Characteristics

Specific Gravity @ 60F	1.125
Boiling Pt., F	265
Freezing Pt., F	-34
pH	10.8
Water Content, wt. %	50
Ash, wt. %	0.6
Color	Green
Foaming Characteristics ml./sec.	50/5



Warren Oil Company, Inc

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301