



Autoguard™ High Mileage Motor Oil

AUTOGUARD HIGH MILEAGE MOTOR OILS are premium passenger car motor oils (PCMO) formulated to protect older engines and extend engine life. **AUTOGUARD HIGH MILEAGE MOTOR OILS** are available in 5W-20, 5W-30 and 10W-30 viscosity grades and are blended with selected and highly refined base oils compounded to provide protection against wear and corrosion, prevent oxidative thickening and inhibit formation of engine acids, sludge and varnish deposits.

AUTOGUARD HIGH MILEAGE MOTOR OILS may be used over a wide temperature range and are formulated to meet the requirements of high mileage vehicles that have accumulated over 75,000 miles and may be experiencing an increase in oil consumption or an increase in leakage.

AUTOGUARD HIGH MILEAGE MOTOR OILS are engineered to protect against high temperature oxidation and provide maximum viscosity protection, minimize start-up wear, and control engine deposits. They are also designed to increase fuel economy, lower engine operating temperatures and extend engine life. Please refer to your service manual for manufacturer's API Service recommendations.

Exceeds requirements of API Service Category SM, SL, SJ, SH or SG.

Benefits

- Helps reduce oil consumption and leaks
- Conditions engine seals
- Protects worn engine parts



Warren Oil Company, Inc

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301



Autoguard™ High Mileage Motor Oil

Typical Characteristics:

SAE Grade	5W-20	5W-30	10W-30
Specific Gravity	0.8637	0.8605	0.8811
Pounds per gallon	7.194	7.163	7.337
Viscosity			
@ 40 °C, cSt	47.4	62.11	76.3
@ 100 °C, cSt	8.1	10.46	11.2
Viscosity Index	142	158	135
Pour Point °F	-35	-30	-30
API Service Category	SM	SM	SM



Warren Oil Company, Inc

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301