



Autoguard[®] Synthetic Blend GF-4 Motor Oils

AUTOGUARD SYNTHETIC BLEND GF-4 MOTOR OILS are premium-quality, high detergent automotive engine oils specially formulated to meet the stringent lubrication demands of today's engines. A unique blend of synthetic and high viscosity index Group II mineral oils combined with a carefully selected additive package, provide maximum protection against wear, rust, corrosion, oxidative thickening, acid formation, sludge and varnish deposits.

AUTOGUARD SYNTHETIC BLEND GF-4 MOTOR OILS meet or exceed the requirements of MIL-1-46152E, Ford WSS-M2C153-H and WSS-M2C930-A (SAE 5W-20) and WSS-M2C929-A (SAE 5W-30)

Meets DaimlerChrysler DC MS10797 (SAE5W-20), DC MS10796 (SAE 5W-30) and DC MS10798 (SAE 10W-30) specifications.

Meets Honda Service Fill Specifications.

Meets the requirements of GM 6094M specification (SAE 5W-20, SAE 5W30 and SAE 10W30).

Meets Toyota Specifications.

Meets API Service Category SM, SL, SJ, SH complies with ILSAC GF-4 requirements.

Benefits

- Blend of synthetic and Group II base oils
- Excellent thermal and oxidation stability
- Protects against rust and corrosion
- Outstanding low temperature pour point
- ILSAC GF-4 Energy Conserving



Warren Oil Company, Inc

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301



Autoguard[®] Synthetic Blend GF-4 Motor Oils

Typical Characteristics

Autoguard Synthetic Blend Motor Oils	5W-20	5W-30	10W-30
Viscosity			
@40 Deg. C, cSt	47.5	60.9	66.4
@100 Deg. C, cSt	8.2	10.4	10.5
Viscosity Index	146	160	146
API Gravity	32.5	33.6	31.1
Sp. Gravity	0.8618	0.8560	0.8692
Pounds per gallon	7.19	7.14	7.24
Flash, COC, °F	405	405	405
Pour Pt., °F	-40	-40	-35
API Performance	SM	SM	SM



Warren Oil Company, Inc

Dunn, NC 28334; Benton, AL 36758; San Antonio, TX 78210;
Marion, IL 62959; Johnstown, PA 15909; West Memphis, AR 72301