



Coastal Full Synthetic AW 46 Hydraulic Oil

Coastal Full Synthetic AW 46 Hydraulic Oil is a premium quality anti-wear hydraulic oil, which is formulated using advanced zinc based anti-wear additive technology, combined with full synthetic base oils, including PolyAlphaOlefin (PAO).

Coastal Full Synthetic AW 46 Hydraulic Oil recommended applications: Cincinnati Lamb (Milacron) P-70, Parker Hannifin (Denison) HF-0, HF-1 and HF-2, Eaton (formerly Vickers) M-2950-S and I-286-S, Passes Vickers 35VQ25 and V104C (ASTM D2882) vane pump tests, passes Denison P-46 piston pump and T-6C vane pump tests, U.S. Steel 127 and 136, and DIN 51524 Part II.

Benefits

- High Viscosity Index (VI) for increased temperature range
- Excellent wear protection
- Outstanding oxidation and thermal stability for long life
- Rapid release of entrained air
- Excellent rust and corrosion protection
- Easy filterability



Warren Oil Company, Inc

*Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301*



Coastal Full Synthetic AW 46 Hydraulic Oil

Typical Characteristics

| | |
|-----------------------------|-------------|
| ISO Viscosity Grade | 46 |
| Gravity, °API | 35.7 |
| Specific Gravity | 0.8457 |
| Flash Point °F (°C) | 460 (238) |
| Pour Point °F. | <-40 |
| Appearance | Light Amber |
| Viscosity | |
| @ 40 °C, cSt | 47.1 |
| @ 100 °C, cSt | 8.35 |
| Viscosity Index | 154 |
| Oxidation, ASTM D943, hours | 5000+ |

| Package | Product Code # |
|---------|----------------|
| Bulk | 00900 |
| Tote | 00998 |



Warren Oil Company, Inc

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301