



Coastal[®] Premium AW 22 Hydraulic Oil

Coastal Premium AW 22 Hydraulic Oil is a premium-quality anti-wear hydraulic oil with excellent stability, designed to meet the most stringent requirements of most all major manufacturers and users of hydraulic equipment, where an ISO 22 fluid is required. **Coastal Premium AW 22 Hydraulic Oil** is characterized by outstanding rust protection, low deposit formation, good demulsibility, rapid release of entrained air, oxidation resistance, low pour points and good anti-foam properties. It also contains an effective anti-wear agent that helps reduce wear in high-speed, high-pressure vane and gear pumps.

Benefits

- Excellent wear protection
- Rapid release of any entrained air
- Excellent rust and corrosion protection
- Easy filterability

Typical Characteristics

	22
SAE Viscosity Grade	5W
Specific Gravity	.863
Flash Point °F (°C)	375 (190)
Pour Point °F.	-30
Viscosity	
@ 40 °C, cSt	22
@100 °C, cSt	4.3
@ 100 °F, SUS	105
@ 210 °F, SUS	39
Viscosity Index	100
Gravity, °API	32.5
Rust Test, ASTM D665	Pass
Oxidation, ASTM D-943	5000 +



Warren Oil Company, LLC

Dunn, NC 28334; Benton, AL 36758; San Antonio, TX 78210;
Marion, IL 62959; Johnstown, PA 15909; West Memphis, AR 72301