



Coastal SAE 30 and SAE 40 API SP Motor Oils

COASTAL SAE 30 AND SAE 40 MOTOR OILS are high detergent single grade lubricants designed with detergent dispersant additives for gasoline engines. A blend of high viscosity index mineral oils combined with a carefully selected additive package provide excellent protection against wear, rust, corrosion, oxidative thickening, acid formation, sludge and varnish deposits. API SP helps prevent pre-ignition and wear and provides improved cleanliness and fuel economy. Meets or exceeds API Service SP and all previous categories. Check owner's manual for proper SAE grade and API Classification.

- Helps fight wear, sludge buildup and deposits
- Helps keep engine running cleaner and more efficiently
- Helps prevent engine rust and corrosion

Typical Characteristics:

SAE Grade	SAE 30	SAE 40
API Gravity @ 60°F	28.9	28.5
Sp. Gr. @ 60°F	.8815	.8836
Flash, COC, °F	420	430
Pour Pt., °F	-20	-20
Viscosity, cSt @ 40°C	95.4	124
Viscosity, cSt @ 100°C	11.0	13.0
Viscosity Index	100	98
API Service Category	SP	SP



Warren Oil Company, LLC

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301