



Coastal[®] Synthetic 2-Cycle Engine Oil

Coastal Synthetic 2-Cycle Engine Oil is formulated with highly refined synthetic base oils and a sophisticated additive system. It is designed to protect today's longer running engines that operate under severe conditions. **Coastal Synthetic Two-Cycle Engine Oil** exceeds the most stringent current specifications including JASO FD, API TC, as well as ISO-L-EGD. **Coastal Synthetic 2-Cycle Engine Oil** provides significantly reduced smoke, improved lubricity, enhanced detergency, and decreased exhaust port deposits. For use in all two-stroke air cooled engines, with unleaded fuel. Meets all manufacturers' requirements for ratios up to 50:1. Formulated with a fuel stabilizer, for longer shelf life after mixing with gasoline.

Fuel Mixing Table

| Ratio Gas to Oil | 1 Gal. oz. | 2 Gal. oz. | 3 Gal. oz. | 4 Gal. oz. | 5 Gal. oz. |
|------------------|------------|------------|------------|------------|------------|
| 16:1 | 8 | 16 | 24 | 32 | 40 |
| 32:1 | 4 | 8 | 12 | 16 | 20 |
| 40:1 | 3.2 | 6.4 | 9.6 | 12.8 | 16 |
| 50:1 | 2.6 | 5.1 | 7.7 | 10.2 | 12.8 |



Warren Oil Company, LLC

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301



Coastal[®] Synthetic 2-Cycle Engine Oil

Typical Characteristics

| | |
|-------------------------|-----------------|
| Viscosity | |
| @40 °C, cSt | 42.0 |
| @100 °C, cSt | 7.5 |
| Viscosity Index | 135 |
| Color | Dark Green/Blue |
| Pour Point °F | -39°F |
| API Gravity | 32.0 |
| Density – pounds/gallon | 7.20 |
| Typical Flash Point | 210°F |



Warren Oil Company, LLC

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301