



## Enviroil<sup>®</sup> DexMerc<sup>™</sup> Automatic Transmission Fluid

**ENVIROIL DEXMERC ATF** is an exceptionally high quality Automatic Transmission Fluid made from re-refined base stocks. This recycling process requires up to 85% less energy to produce, than product made from crude oil. This high Quality base oil is compounded with modern additive technology for use in Ford and General Motors vehicles, as well as many foreign vehicles requiring DEXRON<sup>®</sup>, DEXRON<sup>®</sup>-III (H), (G), III, IIE, II or MERCON<sup>®</sup>. It is recommended for use in all 2005 and earlier GM automatic transmissions. Not for use where DEXRON<sup>®</sup>-VI is required. Recommended for 1981 and later Fords (except those requiring TYPE F, MERCON<sup>®</sup>V, MERCON<sup>®</sup> SP or MERCON<sup>®</sup> LV). It may also be used in applications calling for Allison TES 389. Not for use in Continuously Variable Transmissions (CVT) or Double Clutch Transmissions (DCT). Always check owner's manual for proper application.

### Benefits

- Excellent low temperature fluidity for good cold-start shifting
- Resistance to foaming
- Oxidation and thermal stability for long life
- Protection against rust, corrosion and wear
- Multiple approvals for lower inventory requirements
- Compatible with all transmission seal material

DEXRON<sup>®</sup> is a registered trademark of General Motors Corporation

MERCON<sup>®</sup> is a registered trademark of Ford Motor Company



**Warren Oil Company, Inc**

Dunn, NC 28334; Benton, AL 36758; San Antonio, TX 78210;  
Marion, IL 62959; Johnstown, PA 15909; West Memphis, AR 72301



# Enviroil<sup>®</sup> DexMerc<sup>™</sup> Automatic Transmission Fluid

## Typical Characteristics

Appearance	Red
Viscosity	
@ 40 °C, cSt	37.0
@ 100 °C, cSt	7.2
@ 100 °F, SUS	164
@ 210 °F, SUS	49.7
Viscosity Index	161
Pour Point, °F	-50
Flash Point COC, °F	380



**Warren Oil Company, Inc**

Dunn, NC 28334; Benton, AL 36758; San Antonio, TX 78210;  
Marion, IL 62959; Johnstown, PA 15909; West Memphis, AR 72301