



Synthetic Blend GF-6A Motor Oil

GOLDEN STATE SYNTHETIC BLEND GF-6A MOTOR OILS are premium-quality, high detergent automotive engine oils specially formulated to meet the stringent lubrication requirements of today's engines. A unique blend of synthetic and high viscosity index Group II mineral oils combined with a carefully selected additive package, provide maximum protection against wear, rust, corrosion, oxidative thickening, acid formation, sludge and varnish deposits. API SP provides emission system, turbocharger, LSPI and timing chain protection. Also helps to protect engines when operating on ethanol-containing fuels up to E85.

COASTAL SYNTHETIC BLEND GF-6A MOTOR OILS meet or exceed the requirements of GM 6094M (5W-30, 10W-30) and Ford WSS-M2C961-A1 (SAE 5W-30), Chrysler MS-6395 (5W-30, 10W-30). Meets Toyota Specifications, and Honda Service Fill Specifications (SAE 5W-30 and SAE 10W-30).

Both grades meet or exceed API Service Category SP, SN Plus, SN, SM, SL, SJ, and comply with ILSAC GF-6A requirements.

Benefits

- Improved fuel economy
- Increased sludge protection
- Enhanced piston cleanliness
- Increased emission protection
- ILSAC GF-6A Resource Conserving formula



Warren Oil Company, LLC

Dunn, NC 28334; Benton, AL 36758; San Antonio, TX 78210;
Marion, IL 62959; Johnstown, PA 15909; West Memphis, AR 72301



Synthetic Blend GF-6A Motor Oil

Typical Characteristics:

SAE Grade	5W-30	10W-30
API Gravity @ 60°F	33.1	30.1
Sp. Gr. @ 60°F	.8595	.8702
Flash, COC, °F	420	430
Pour Pt., °F	-38	-30
Viscosity, cSt @ 40°C	60.8	68.2
Viscosity, cSt @ 100°C	10.2	10.3
Viscosity Index	156	137
API Service Category	SP	SP
ILSAC	GF-6A	GF-6A



Warren Oil Company, LLC

Dunn, NC 28334; Benton, AL 36758; San Antonio, TX 78210;
Marion, IL 62959; Johnstown, PA 15909; West Memphis, AR 72301