



LubriGold® Full Synthetic SAE 0W-20 API SP Motor Oil Approved for dexos1™ Gen 2

LubriGold Full Synthetic SAE 0W-20 API SP Motor Oil is approved for **GM dexos1™ Gen 2**. It is a top tier, high detergent automotive engine oil specially formulated to meet the stringent lubrication requirements of today's engines. Synthetic base oils combine with carefully selected additive packages to provide maximum protection against wear, rust, corrosion, oxidative thickening, acid formation, sludge and varnish. API SP provides emission system, turbocharger, LSPI and timing chain protection. Also helps to protect engines when operating on ethanol-containing fuels up to E85.

LubriGold Full Synthetic SAE 0W-20 API SP Motor Oil is a licensed **GM dexos1™ Gen 2** product (GM License # D125BABA028). It is suitable for use in applications calling for Ford WSS-M2C947-B1. Meets or exceeds API Service Category SP, SN PLUS, SN, SM, SL, SJ and ILSAC GF-6A requirements. Exceeds the performance requirements of Toyota and Honda.

Benefits

- Formulated to reduce friction and provide increased fuel economy
- Protects engine in all temperatures and conditions
- Keep precision parts running clean
- ILSAC GF-6A Resource Conserving



Warren Oil Company, LLC

Dunn, NC 28334; Benton, AL 36758; San Antonio, TX 78210;
Marion, IL 62959; Johnstown, PA 15909; West Memphis, AR 72301



**LubriGold® Full Synthetic
SAE 0W-20 API SP Motor Oil
Approved for dexos1™ Gen 2**

Typical Characteristics:

SAE Grade	0W-20
API Gravity @ 60°F	36.0
Sp. Gr. @ 60°F	0.8448
Flash, COC, °F	440
Pour Pt., °F	-50
Viscosity,	
cSt @ 40°C	46.0
cSt @ 100°C	8.9
Viscosity Index	178
API Performance	SP
ILSAC	GF-6A
Blend Site	WM
GM dexos1™ Gen 2 License Number	D125BABA028
Part Number	
6/1 qt	401400
6 gal box	401585
55 gal drum	401523
275 gal tote	401561
Bulk	30000



Warren Oil Company, LLC

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301