



LubriGold[®] Full Synthetic GF-5/SN Motor Oils

LubriGold Full Synthetic GF-5/SN Motor Oils are top tier, high detergent automotive engine oils specially formulated to meet the stringent lubrication requirements of today and tomorrow's engines. They meet API SN which is required for 2012 and later engines. Synthetic base oils combine with carefully selected additive packages to provide maximum protection against wear, rust, corrosion, oxidative thickening, acid formation, sludge and varnish.

LubriGold Full Synthetic GF-5/SN Motor Oils meet or exceed the requirements of GM 6094M (SAE 0W-20, 5W-20, 5W-30, 10W-30) and Ford WSS-M2C945-A (SAE 5W-20) and WSS-M2C946-A (SAE 5W-30), Chrysler MS-6395 (SAE 0W-20, 5W-20, 5W-30, 10W-30). Meets Toyota Specifications, and Honda Service Fill Specifications (SAE 0W-20, SAE 5W-20, SAE 5W-30 and SAE 10W-30).

LubriGold High Performance SAE 5W-30 is a licensed GM dexos1[®] product (GM License # RB1E0709028). GM dexos1[®] supersedes GM4718M, and GM6094M.

All grades meet or exceed API Service Category SN, SM, SL, SJ and comply with ILSAC GF-5 requirements.

Benefits

- Our highest level of protection for thermal and oxidation stability
- Formulated for extreme driving conditions
- Outperforms conventional and synthetic blends
- Outstanding low and high temperature performance
- ILSAC GF-5 Resource Conserving



Warren Oil Company, Inc

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301



LubriGold[®] Full Synthetic GF-5/SN Motor Oils

Typical Characteristics:

LubriGold Full Synthetic GF-5/SN Motor Oils				
SAE Grade	0W-20	5W-20	HP 5W-30	10W-30
API Gravity @ 60°F	34.9	34.8	34.5	33.0
Sp. Gr. @ 60°F	0.8504	0.8510	0.8518	0.8520
Flash, COC, °F	405	405	446	405
Pour Pt., °F	-48	-40	-50	-35
Viscosity,				
cSt @ 40°C	45.0	46.6	53.3	62.8
cSt @ 100°C	8.5	8.4	10.0	10.5
Viscosity Index	170	160	177	156
Zinc, Wt. %	0.856	0.810	0.810	0.820
Phosphorus, Wt. %	.0767	.0740	.0740	.0746
API Performance	SN	SN	SN	SN
Part Number				
6/1 qt	402001	402056	402100	402155
6 gal box	-	-	403565	-
55 gal drum	405019	405026	405033	405040
275 gal tote	405098	405198	406030	405298
Bulk	405000	402000	20000	402200



Warren Oil Company, Inc

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301