



Lubriguard™ Extreme Duty Hi-Temp EP Grease

LUBRIGUARD EXTREME DUTY HI-TEMP EXTREME PRESSURE GREASES are NLGI #1 and NLGI #2 grade greases recommended for extreme duty off-highway applications. Formulated to cling tenaciously to surface metal and provide long lasting protection and lubrication under the harshest conditions.

Benefits

- Premium quality lithium complex, Extreme Pressure (EP) grease
- High base oil viscosity for greater wear protection
- Outstanding protection in wet environments
- “Tacky”, stay in place formula clings tenaciously
- Superior protection to lubricate a wide variety of severe duty on and off highway, industrial, mining and construction applications
- Available in NLGI #1 and NLGI #2 grades

Part Numbers:	#1 Grade	#2 Grade
50/14 Ounce Tubes	703405	703351
35 Lb. Pail	703429	703375
120 Lb.	703573	703566
400 Lb. Drum	703436	703382
2000 Lb. Tote	703443	703399



Warren Oil Company, LLC

*Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301*



LubriGuard™ Extreme Duty Hi-Temp EP Grease

Typical Characteristics:

NLGI Consistency Number	1	2
NLGI Rating	GC/LB	GC/LB
Thickener	Lithium Complex	Lithium Complex
Texture	Smooth, Tacky	Smooth, Tacky
Color, Observed	Red	Red
Worked 60 Penetration, D-217	310 - 340	265 - 295
Dropping Point, D-566, °F	515	525
Base Oil Viscosity @ 40°C, cSt	620	620
Water Washout, D-1264, % loss @ 175°F	5.0	3.82
Copper Corrosion, ASTM D-4048, rating	1B	1B
Rust Prevention, ASTM D1743, rating	Pass	Pass
Oil Separation, D-1742, % loss	2.5	1.8
Four-Ball Wear, ASTM D-2266, mm	0.45	0.45
Four-Ball EP Weld Point, D-2596, kgf	315	315
Four-Ball Load Wear Index, D-2596, kgf	50	50
Timken OK Load, ASTM D-2509, lb.	60	70+
Approximate Temperature Range, °F	0 to 325	0 to 325



Warren Oil Company, LLC

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301