

## Lubriguard™ Synthetic SAE 40 Heavy Duty Manual Transmission Fluid

Lubriguard Synthetic SAE 40 Heavy Duty Manual Transmission Fluid is a specially formulated synthetic lubricant designed for fuel efficiency, extended drain intervals and severe service in heavy duty commercial vehicle transmissions which require a non-EP transmission lubricant. It is specially formulated to protect high torque transmissions coupled with increased horsepower engines. It is approved for use in Eaton transmissions such as Ultrashift Plus, Fuller Advantage, FR and RT Series transmissions. It is not suitable for hypoid gear applications in differentials and final drives, either for topping-off or refills, where API Service GL-5 or SAE J2360 lubricants are specified.

## **Benefits**

- Up to 1.5% fuel economy improvement
- Provides high performance and extended drain capabilities
- Excellent shear stability to ensure smooth transmission operation
- Excellent thermal and oxidation stability
- Eaton PS-386 (supersedes PS-164 Rev 7)
- Mack TO-A Plus
- Navistar MPAPS B-6816 Type II
- API MT-1

⚠WARNING: This product can expose you to chemicals including ANILINE, which is known to the State of California to cause cancer, and TOLUENE, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to <a href="https://www.P65Warnings.gov">www.P65Warnings.gov</a>



Warren Oil Company, LLC

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210: Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301



## Lubriguard<sup>™</sup> Synthetic SAE 40 Heavy Duty Manual Transmission Fluid

## **Typical Characteristics:**

SAE Viscosity Grade		40
Viscosity	ASTM D 445	
@ 40°C, cSt		95.1
@100°C, cSt		14.8
Viscosity Index	ASTM D 2270	163
Pour Point, °F (°C)	ASTM D 97	-44 (-42)
Flash Point, °F (°C)	ASTM D 92	460 (238)
Gravity, API	ASTM D 287	34.9



Package	Product Code #
Bulk	33104
Drum	702781
Keg	702774
Pail	702767



Warren Oil Company, LLC