



Lubriguard™ Heavy Duty Prediluted Antifreeze & Coolant

LUBRIGUARD™ Heavy Duty Prediluted Antifreeze & Coolant is an advanced NOAT (Nitrited Organic Acid Technology) formulated, ethylene glycol based coolant using organic acid inhibitors to provide extended life protection for heavy-duty diesel, gasoline and natural gas engine cooling systems. It's phosphate-free, silicate-free and borate-free non-abrasive formula can improve water pump seal life and provides outstanding protection against corrosion and cavitation. Eliminates drop-out, gel and reduces scale. Provides excellent heat transfer for high temperature applications such as engines with EGR and SCR systems. With proper maintenance* LUBRIGUARD™ Heavy Duty Prediluted Antifreeze & Coolant delivers cooling system protection for up to 750,000 miles of on-road use (8 years or 15,000 hours of off-road use) without the use of Supplemental Coolant Additives (SCAs) or chemically charged filters.

*Proper maintenance requires a complete cooling system flush and fill and subsequent topping off, as needed with LUBRIGUARD™ Heavy Duty Prediluted Antifreeze & Coolant. Follow manufacturer's recommendations for specified maintenance.

Meets or exceeds the following specifications: ASTM D6210, ASTM D4340, ASTM D3306, TMC RP329, TMC RP351 (COLOR).

Recommended for use in heavy-duty vehicles and stationary equipment, regardless of fuel type, including: • CAT EC-1 • CUMMINS CES 14603 • JOHN DEERE H24A2, H24C2 • NAVISTAR • PACCAR • VOLVO/MACK • JI CASE • KOMATSU • INTERNATIONAL • GM • WAUKESHA • FORD • NEW HOLLAND • FREIGHTLINER.

Product Color: Red

Freezing Point: -34°F

Boiling Point: +265°F



Warren Oil Company, LLC

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301