



LUBRIGUARD™ HEAVY DUTY SYNTHETIC GEAR AND TRANSMISSION LUBRICANTS DANA, MERITOR, AND DETROIT APPROVED

Lubriguard Heavy Duty Synthetic Gear Lubricants are full synthetic heavy-duty gear and bearing lubricants. These products will find applications in transfer cases and differentials of trucks, buses, passenger cars, and construction and agriculture equipment. The outstanding oxidation resistance of these products provide for extended oil drain intervals. They are available in two viscosity grades: SAE 75W-90 and SAE 80W-140.

Lubriguard Heavy Duty Synthetic Gear Lubricants are recommended for heavy-duty axles and final drives requiring SAE J2360, API GL-5 & MT-1 performance. These products are approved for use in Dana (formerly Eaton Roadranger) Meritor, Detroit, Mack and Navistar to maintain extended warranties with oil drains of up to 500,000 miles. These products are not intended for use in automatic, manual or semi-automatic transmissions for which engine oil or automatic transmission fluids are recommended.

Benefits

- Approved for extended warranties and extended drain intervals
- Exceptional low temperature fluidity
- Enhanced friction reducing properties
- Long service life
- Reduces drag for optimum fuel economy
- Manufactured with Full Synthetic PAO (Group IV) Base Oils

⚠️WARNING: This product can expose you to chemicals including ANILINE, which is known to the State of California to cause cancer, and TOLUENE, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.gov



Warren Oil Company, LLC

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301



LUBRIGUARD™ HEAVY DUTY SYNTHETIC GEAR AND TRANSMISSION LUBRICANTS DANA, MERITOR, AND DETROIT APPROVED

Typical Characteristics:

| Lubriguard Heavy Duty Synthetic | 75W-90 | 80W-140 |
|--|---------------|----------------|
| Viscosity | | |
| @100 Deg. C, cSt | 15.0 | 29.0 |
| Viscosity Index | 152 | 151 |
| Density @ 15°C | 0.886 | 0.894 |
| Pounds per gallon | 7.39 | 7.45 |
| Foam Seq. I, II, III | PASS | PASS |
| Pour Pt., °C | -42 | -33 |
| Flash, COC, °C | 215 | 186 |
| API GL-5/MT-1 | X | X |
| Former Eaton Roadranger E500 | X | X |
| Dana SHAES 256 Rev E | X | |
| Dana SHAES 429 Rev A | X | X |
| Daimler / Detroit DFS93K219.01 | X | |
| Mack GO-J Plus | X | |
| Mack GO-J | | X |
| Navistar MPAPS B-6821 | X | X |
| Meritor 0-76N | X | |
| Meritor 0-76-B | | X |
| Meritor 0-80 | | X |
| International TMS-6816 | X | X |
| SAE J2360 (Mil-PRF-2105E) | X | X |
| Product Code # | | |
| Bulk | 33102 | 33103 |
| Tote | 702798 | |
| Drum | 702743 | 702699 |
| Keg | 702729 | 702736 |
| Pail | 702620 | 702644 |



Warren Oil Company, LLC

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301