



## **SAXON<sup>®</sup> GOLD Synthetic Blend SN 10W-40 & 20W-50 Motor Oil**

**SAXON GOLD Synthetic Blend Motor Oils in 10W-40 and 20W-50** are formulated to provide engine protection under severe operating conditions. **Saxon Gold Synthetic Blend Motor Oils** are blended from selected and highly refined base oils compounded to provide protection against wear and corrosion, prevent oxidative thickening and inhibit promotion of engine acids, sludge and varnish deposits.

**SAXON GOLD Synthetic Blend Motor Oils in 10W-40 and 20W-50** may be used over a wide temperature range. They also permit easier cold weather starting and help minimize engine friction at start-up.

Recommended for automotive gasoline engines, including those equipped with superchargers, used in passenger cars, light trucks, power boats, and other mobile and stationary equipment. Always check owner's manual for proper application.

Meets API Service Category SN, SM, SL, SJ

### **Benefits**

- Resisted breakdown under high temperatures
- Maintained oil pressure under heavy load conditions
- Minimized rust and corrosion
- Good low temperature pour point



**Warren Oil Company, Inc**

*Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:  
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301*



## **SAXON<sup>®</sup> GOLD Synthetic Blend SM 10W-40 & 20W-50 Motor Oil**

### **Typical Characteristics**

<b>SAXON GOLD</b>	<b>10W-40</b>	<b>20W-50</b>
API Gravity	31.0	29.4
Sp. Gravity	0.8707	0.8786
Viscosity		
@40 Deg. C, cSt	91.5	165.5
@100 Deg. C, cSt	14.1	18.8
Viscosity Index	151	128
Pour Point Deg. F	-22	-11
Flash, COC, °F	410	405
API Performance	SN	SN



**Warren Oil Company, Inc**

*Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:  
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301*