



## Saxon Gold<sup>®</sup> Synthetic Blend GF-5 Motor Oil

---

**SAXON GOLD SYNTHETIC BLEND GF-5 MOTOR OILS** are premium-quality, high detergent automotive engine oils specially formulated to meet the stringent lubrication requirements of today's engines. A unique blend of synthetic and high viscosity index Group II mineral oils combined with a carefully selected additive package, provide maximum protection against wear, rust, corrosion, oxidative thickening, acid formation, sludge and varnish deposits.

**SAXON GOLD SYNTHETIC BLEND GF-5 MOTOR OILS** meet or exceed the requirements of GM 6094M (SAE 5W-20, 5W-30, 10W-30) and Ford WSS-M2C945-A (SAE 5W-20) and WSS-M2C946-A (SAE 5W-30), Chrysler MS-6395 (SAE 5W-20, 5W-30, 10W-30). Meets Toyota Specifications, and Honda Service Fill Specifications (SAE 5W-20, SAE 5W-30 and SAE 10W-30).

All grades meet or exceed API Service Category SN, SM, SL, or SJ and comply with ILSAC GF-5 requirements.

### Benefits compared to GF-4

- Improved fuel economy
- Increased sludge protection
- Enhanced piston cleanliness
- Increased emission protection
- ILSAC GF-5 Resource Conserving formula



**Warren Oil Company, Inc**

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:  
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301



## Saxon Gold<sup>®</sup> Synthetic Blend GF-5 Motor Oil

Typical Characteristics:

<b>SAXON GOLD SYNTHETIC BLEND GF-5 MOTOR OIL</b>			
<b>SAE Grade</b>	<b>5W-20</b>	<b>5W-30</b>	<b>10W-30</b>
API Gravity @ 60°F	32.8	32.8	30.9
Sp. Gr. @ 60°F	.8612	.8612	.8713
Flash, COC, °F	428	420	430
Pour Pt., °F	-38	-38	-30
Viscosity, cSt @ 40°C	48.7	58.0	65.7
Viscosity, cSt @ 100°C	8.6	10.2	10.3
Viscosity Index	155	165	144
API Service Category	SN	SN	SN
ILSAC	GF-5	GF-5	GF-5



**Warren Oil Company, Inc**

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:  
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301