



Warren[®] Full Synthetic GL-5 Gear Oils

Warren Full Synthetic GL-5 Gear Oils are multi-purpose gear lubricants designed for API Service Classification “GL-5” and “MT-1”.

Warren Full Synthetic GL-5 Gear Oils are compounded with highly refined synthetic base stocks and additives to ensure extreme pressure characteristics, anti-wear, corrosion inhibition, rust preventions, low pour point, and anti-foaming performance. These products are formulated for use in limited slip differentials.

Warren Full Synthetic GL-5 Gear Oils may be used in applications calling for API GL-5, API MT-1, SAE J2360, and Mack GO-J (75W-140) and Mack GO-J Plus (75W-90).

Warren Full Synthetic GL-5 Gear Oils are recommended for use in limited slip and conventional differentials of heavy duty trucks, cars, light trucks and sport utility vehicles. Always check owner’s manual for proper recommendation. Note: These products are not approved for Eaton Roadranger and ArvinMeritor Extended Warranties. For those applications use LubriGuard Heavy Duty Synthetic Gear Lubricants.

Benefits

- Reduced wear
- Long service life
- Exceptional low temperature performance
- Reduces drag for optimum fuel economy
- Full Limited Slip performance



Warren Oil Company, LLC

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301



Warren[®] Full Synthetic GL-5 Gear Oils

Typical Characteristics

SAE Viscosity Grade		75W-90	75W-140
Pour Point Deg F.		-40	-40
Flash Point, COC, °F		410	420
Viscosity			
@ 40°C, cSt		86.6	178
@ 100°C, cSt		14.8	27.6
Viscosity Index		180	194
Gravity, API		30.6	32.9
Rust Test, ASTM D665		Pass	Pass
Product Code #			
Pail		WAR287358	WAR287365



Warren Oil Company, LLC

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301