



Warren[®] GEO Low Ash AW SAE 15W-40 Engine Oil

Warren GEO Low Ash AW SAE 15W-40 Engine Oil is a high performance low ash engine oil formulated for the lubrication of the crankcase and power compressor cylinders of spark-ignited two-and four cycle gas fueled engines.

Warren GEO Low Ash AW SAE 15W-40 Engine Oil is formulated with high quality hydrocracked base stocks, combined with a high performance additive package containing ashless dispersants, oxidation and corrosion inhibitors, antifoam and antiwear agents. It is suitable for use in engines burning gaseous fuels such as clean natural gas, sour gas, sewer gas, well-head gas, methane, ethane and others. This oil meets the performance requirements of mobile compressed natural gas engine manufacturers such as Cummins and Detroit Diesel. It is suitable for use for engines equipped with turbochargers and/or catalytic converters. This product is approved by Cummins for CES 20074 applications.

Typical Characteristics

SAE Viscosity	15W-40
@40 °C, cSt	120
@100 °C, cSt	15.6
Viscosity Index	137
API Gravity	30.5
Sp. Gravity	0.8735
Flash, COC, °F	450
Pour Pt., °F	-31
Sulfated Ash	0.54
Zinc, ppm	800
Phosphorus, ppm	730
Calcium, ppm	1179
TBN, ASTM D2896	5.6
Product Code #	
Bulk	015410
Tote	015498
Drum	015412



Warren Oil Company, LLC

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301