



Warren[®] Multi-Purpose DexMerc[®] ATF

WARREN MULTI-PURPOSE DexMerc ATF is manufactured from highly refined base stocks and compounded with modern additive technology for use in older Ford and General Motors vehicles, as well as many foreign vehicles, requiring DEXRON[®]-III or MERCON[®].

Recommended for use in 2005 and earlier GM automatic transmissions. Not for use where DEXRON[®]-VI or DEXRON[®]-HP are required.

Recommended for 1981 and later Fords (except those requiring Type F, MERCON[®] V, MERCON[®] SP, MERCON[®] LV or MERCON[®] ULV). Not for use in Continuously Variable Transmissions (CVT) or Dual Clutch Transmissions (DCT). Always check owner's manual for proper recommendation.

Benefits

- Excellent low temperature fluidity for good cold-start shifting
- Resistance to foaming
- Oxidation and thermal stability for long life
- Protection against rust, corrosion and wear
- Compatible with all transmission seal material

DEXRON[®] is a registered trademark of General Motors Corporation.
MERCON[®] is a registered trademark of Ford Motor Company.



Warren Oil Company, LLC

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301



Warren[®] Multi-Purpose DexMerc[®] ATF

Typical Characteristics

WARREN MULTI-PURPOSE DexMerc ATF	
Appearance	Red, Dyed
Viscosity	
@ 40 °C, cSt	33.37
@ 100 °C, cSt	6.87
Viscosity Index	161
Pour Point, °F	-50
API Gravity	33.0
Specific Gravity @ 60°F	0.8602
Pounds per gallon	7.163
Flash Point COC, °F	405
Allison C-4	Y
Cat TO-2	Y



Warren Oil Company, LLC

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301