



Warren[®] Sawguide Oil

WARREN SAWGUIDE OIL - is formulated to provide excellent lubricity and provide protection against rust and corrosion for saw and guide components. It contains a tackiness additive which causes it to cling tenaciously to the components providing protection against friction and wear and reduced lubricant consumption. The additive package provides outstanding demulsibility, to separate the oil and water.

WARREN SAWGUIDE OIL - is recommended for use on gang saws, edgers and modern thin kerf saw systems.

Benefits

- Protects against friction and wear
- Exceptional protection against rust and corrosion
- Resists water wash-off
- Outstanding demulsibility
- Non-corrosive to metals
- Helps reduce lubricant consumption



Warren Oil Company, LLC

Dunn, NC 28334; Benton, AL 36758; San Antonio, TX 78210;
Marion, IL 62959; Johnstown, PA 15909; West Memphis, AR 72301



Warren[®] Sawguide Oil

Typical Characteristics:

ISO Grade	100	150
Gravity, API	29.2	29.6
Specific Gravity	0.8724	0.8783
Viscosity		
@ 40 Deg. C, cSt	100	158
@100 Deg. C, cSt	11.3	15.6
@100 Deg. F, SUS	521	732
@ 210 Deg. F, SUS	63	80
Viscosity Index	99	100
Pour Point Deg. F	-10	0
Flash Point Deg. F	475	475
Rust Test	PASS	Pass



Warren Oil Company, LLC

Dunn, NC 28334; Benton, AL 36758; San Antonio, TX 78210;
Marion, IL 62959; Johnstown, PA 15909; West Memphis, AR 72301