

# WARREN OIL COMPANY, INC.

## MATERIAL SAFETY DATA SHEET

Warren Oil Company, Inc.  
Hwy 301 North  
PO Box 1507  
Dunn, NC 28335  
910-892-6456

*Product:* Warren Fuel Injector/Carburetor Cleaner

---

### **Section 1: Product Identification**

---

*Chemical Name:* Petroleum Naphtha Mixture  
*Synonym(s)/Common Name(s):* Carb & Injector Cleaner

*Chem Formula:* Proprietary  
*CAS Number:* NA

*DOT Ship Name:* Flammable Liquid N.O.S.  
*DOT Haz Class:* 3.3  
*DOT ID Number:* UN1993

*Chemtrec:* 1-800-CMA-8200

*IMCO Ship Name:* Flammable Liquids N.O.S. (Naphtha, Petroleum)  
*IMCO Hazard Class:* 3.3  
*IMCO I.D. #:* 1993

*IMCO Page Number:* 3345

*Hazard Ratings:* Health 1 Flammability 2 Reactivity 0

---

### **Section 2: Hazardous Ingredients**

---

<b>Ingredient</b>	<b>OSHA PEL/ACGIH TLV</b>	<b>CAS Number</b>	<b>Percent</b>
Mineral Spirits	NA/350 mg/m <sup>3</sup>	8052-41-3	>80.00
Heavy Aromatic Naphtha	5 mg/cu meter/ NA	64742-94-5	<5.00
Severely Hydrotreated Naphthenic Distillate	NA/NA	64742-52-5	<15.00
Naphthalene	50/52	91-20-3	<1.00

---

### **Section 3: Physical Characteristics**

---

*pH:* No data  
*Viscosity:* No data

---

### **Section 4: Fire and Explosion**

---

*Autoignition Temperature:* Not determined.

*Decomposition Products Under Fire Conditions:* May liberate carbon monoxide, carbon dioxide, and unidentified

organic compounds in black smoke. Materials to avoid include oxidizing agents.

*“Empty” Container Warning:* Dispose of contaminated product and materials used in cleaning up spills or leaks in a manner approved for this material. Consult appropriate Federal, State and Local regulatory agencies to ascertain proper disposal procedures.

*Note:* Empty containers have residues, gases and mists and are subject to proper waste disposal, as above.

*Extinguishing Media and Fire Fighting Procedures:* Use water fog, dry chemical, foam or CO<sub>2</sub>. Do not use a direct water stream.

*Flash Point (min.):* 101 deg F.

*Flammable or Explosive Limits (APRX. % by volume in air):*

*Lower: 1*

*Upper: 6*

---

### **Section 5: Reactivity Data**

---

*Reactivity*

*Stability:* Stable.

*Polymerization:* Will Not Occur

*Materials to Avoid:* Oxidizing agents.

*Hazardous Decomposition Products:* May liberate carbon monoxide, carbon dioxide, and unidentified organic compounds in black smoke.

---

### **Section 6: Health Hazard Data**

---

*Effect of Overexposure (Signs and Symptoms of Exposure):* Inhalation of higher concentrations may cause headaches, nausea, and vomiting. Inhalation of very high concentrations or prolonged exposure may cause unconsciousness.

*Eye Contact:* Immediately flush eyes with lots of running water for 15 minutes, lifting the upper and lower eyelids occasionally. Get immediate medical attention.

*Ingestion:* Do not induce vomiting. Get immediate medical attention. If vomiting occurs spontaneously, keep victim's head low below his hips to prevent his breathing the vomitus into his lungs.

*Inhalation:* Remove to fresh air. Give artificial respiration if not breathing. Get immediate medical attention.

*Nature of Hazard:* Inhalation: Vapors and mists irritate mucous membranes. Eyes - Liquid and mist may irritate the eyes. Skin - Brief contact may dry the skin. Prolonged or repeated contact may irritate the skin, causing dermatitis. Swallowed - Swallowing the liquid may result in vomiting. If vomiting occurs spontaneously, do not allow vomitus to be breathed into the lungs as even a small quantity in the lungs may result in chemical pneumonitis and pulmonary edema/hemorrhage.

*Skin Contact:* Immediately wash skin with lots of soap and water. Remove contaminated clothing and shoes, wash before reuse. Get medical attention if irritation persists after washing.

*Variability Among Individuals:* None known.

---

### **Section 7: Precautions for Safe Handling and Use**

---

*Precautions for Handling: Precautions to be Taken in Handling and Storage:* Store in tightly closed containers in cool, dry, isolated and well ventilated area away from, heat sources of ignition and incompatible materials. Use nonsparking tools and explosion proof equipment. Ground lines, containers, and other equipment used during product transfer to reduce the possibility of a static induced spark. Do not “switch” load (load into containers which previously contained gasoline or other low flash material) because of possible accumulation of a static charge resulting in a source of ignition. Use good personal hygiene practices. After handling this product, wash hands before eating, drinking, smoking or using toilet facilities.

---

### **Section 8: Industrial Hygiene Control Measures**

---

*Industrial Hygiene Control Measures:* See Section 6, 7, 9

---

### **Section 9: Special Precautions**

---

*Eye Protection:* Chemical goggles..

*Other Protective Equipment:* Long-sleeved shirt, trousers, safety shoes, and rubber apron. Note: An eyewash and safety shower should be nearby and ready for use.

*Personal Hygiene:* Do not breathe vapors. Avoid contact with eyes, skin and clothing. Wear protective clothing including goggles and rubber gloves. Wash promptly when skin is wet, during breaks, and before meals.

*Protective Gloves:* Rubber gloves.

*Respiratory Protection:* NIOSH approved canister respirator in the absence of adequate environmental controls at the point of use. Fire fighters should wear self-contained breathing apparatus. Use water spray to cool nearby containers and structures exposed to fire.

*Spill or Leak Procedures:* Action to take for spill or leaks: Wear protective equipment including rubber boots, rubber gloves, rubber apron, chemical goggles, and respiratory protection. Extinguish all ignition sources and ensure that all handling equipment is electrically grounded. For small spills or drips, mop or wipe up and dispose of in DOT approved waste containers. Keep out of sewers, storm drains, surface waters, and soil. Comply with all applicable governmental regulations on spill reporting, and handling and disposal of waste.

*Ventilation:* Local mechanical exhaust ventilation capable of maintaining emissions at the point of use below the PEL. (OSHA PEL = 500 PPM).

*Work Practices/Engineering Controls:* Keep away from heat, sparks and flames. Store in a cool, dry place. Vent container frequently and more often in warm weather, to relieve pressure. Electrically ground all equipment when handling this product and use only non-sparking tools. Keep container tightly closed when not in use. Do not use pressure to empty container. Wash thoroughly after handling. Do not get in eyes, on skin, or on clothing. Do not cut, weld, drill on or near this container. Containers, even those that have been emptied, will retain product residue and vapors. Always obey hazard warnings and handle empty containers as if they were full.

---

### **Disclaimer**

---

*The information and recommendations contained herein are, to the best of Warren Oil Co., Inc.'s knowledge and belief, accurate and reliable as of the date issued. Warren Oil Company, Inc. does not warrant or guarantee their accuracy or reliability, and Warren Oil Company, Inc. shall not be liable for any damage arising out of the use thereof.*

*It is the user's responsibility to satisfy that the information is suitable and complete for its particular use.*