



# AUTOGUARD 50/50 ANTIFREEZE & COOLANT

Warren Oil Company

Product Data Sheet

AUTOGUARD 50/50 Antifreeze & Coolant is an ethylene glycol base coolant for both automotive aluminum block engines and low silicate heavy duty diesel engines, and is designed to be compatible with SCA's.

AUTOGUARD 50/50 Antifreeze & Coolant Protects all cooling system parts including aluminum and modern high lead solders.

AUTOGUARD 50/50 Antifreeze & Coolant prevents freezing, boil-over, rusting, corrosion, sludge clogging and scale build-up throughout the cooling system.

AUTOGUARD 50/50 Antifreeze & Coolant meets or exceeds the following specifications:

ASTM D-3306  
ASTM D-4340  
Chrysler MS 7170  
Ford ESE-M97B44-A  
G.M. 1825M

SAE J1034  
Caterpillar  
Cummins 90T8-4  
G.M. 1899M  
John Deere H24B1/C1

Mack Truck  
TMC RP 302B  
SAE J1941  
ASTM D-4985  
Volvo/G.M. Heavy Truck

AUTOGUARD 50/50 Antifreeze & Coolant is pre-diluted and ready to use. **DO NOT DILUTE.**

## Typical Characteristics

Specific Gravity @ 60F	1.125
Boiling Pt., F	265
Freezing Pt., F	-34
pH	10.8
Water Content, wt. %	50
Ash, wt. %	0.6
Color	Green
Foaming Characteristics ml./sec.	50/5

**Warren Oil Company, Inc.**

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:  
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301