



## Gold Band<sup>®</sup> Quality AW Hydraulic Oil

**GOLD BAND QUALITY AW HYDRAULIC OILS** are blended with highly refined naphthenic base oils and an additive package that provides excellent antiwear protection and inhibits rusting and corrosion. An antifoam agent has also been added to suppress foaming and air entrainment.

**GOLD BAND QUALITY AW HYDRAULIC OILS** provide many of the advantages of premium hydraulic oil at a moderate price. They help contain operating costs where service requirements do not demand a premium quality product (such as Coastal Premium AW Hydraulic Oils).

**GOLD BAND QUALITY AW HYDRAULIC OILS** are available in three ISO grades (32, 46, & 100) to satisfy the varying requirements of vane, gear, and piston pumps.

### Typical Characteristics

	<b>32</b>	<b>46</b>	<b>68</b>
SAE Viscosity Grade	10W	20W	20W
Specific Gravity	0.878	0.896	0.904
Flash Point °F ( °C )	405 (208)	405 (208)	410 (210)
Pour Point °F.	-30	-15	0
Viscosity			
@ 40 °C, cSt	29.6	44.5	68
@ 100 °C, cSt	4.1	5.5	6.4
@ 100 °F, SUS	155	207	315
@ 210 °F, SUS	39.8	44.3	47.2
Gravity, °API	29.5	26.2	24.8



### Warren Oil Company, Inc

Dunn, NC 28334; Benton, AL 36758; San Antonio, TX 78210;  
Marion, IL 62959; Johnstown, PA 15909; West Memphis, AR 72301