



CHAIN SAW BAR LUBRICANT

Warren Oil Company

Product Data Sheet

ITASCA CHAIN SAW BAR LUBRICANT is a premium lubricant designed especially for the lubrication of bar and chains on chain saws and open enclosed chains on motorcycles, snowmobiles and lawn and garden equipment.

ITASCA CHAIN SAW BAR LUBRICANT are formulated with highly refined base stocks and select additives to assure excellent performance as a chain saw bar and chain lubricant. It is designed with high load-carrying capacity to protect against high pressures generated in the bar and chain during operation. A special tackifier is added to the oil, which promotes good adhesion to moving parts and minimizes oil throw off.

ITASCA CHAIN SAW BAR LUBRICANT are designed to prevent rusting and reduce wear and link breakage thus extending bar and chain life. Penetration into rivet holes and the bat channel is assured. Down-time and cutting interruptions are minimized.

Benefits

- Reduced wear of bar and chain
- Reduced throw off
- Reduces heat build-up
- Excellent rust and corrosion protection
- High load carrying capacity
- Different viscosity weights for various ambient temperatures

Warren Oil Company, Inc.

*Dunn, NC 28334 : Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72303*



***CHAIN SAW BAR
LUBRICANT***

Typical Characteristics

	10W	20W	30W	40W
Gravity, API	32.8	30.8	29.5	28.9
Density,	0.8602	0.8708	0.8777	0.8808
Viscosity				
@ 40 Deg. C, cSt	22.49	51.29	85.97	118.56
@ 100 Deg. C, cSt	4.79	8.21	10.99	13.47
Viscosity Index	138	132	114	109
Pour Point Deg. F	-48	-36	-21	3

Warren Oil Company, Inc.

*Dunn, NC 28334 : Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72303*