



***ITASCA LAWNMOWER &  
UTILITY 4-CYCLE 10W-30***

**Warren Oil Company**

Product Data Sheet

**Itasca Lawnmower & Utility 4-Cycle 10W-30 Motor** provides long-lasting engine protection and meets or exceeds 4-cycle engine requirements. Recommended for lawn and garden tractors, riders, walk-behind mowers, generators, commercial mowers, edgers and other outdoor 4-cycle equipment. Exceeds API Service Specification requirements for SL. Consult owner's manual for manufacturer's recommendations for your engine's requirements.

**Benefits**

- Protect engine under severe operating conditions
- Provides maximum protection at high operating temperatures
- Protects against rust and corrosion
- Exceeds API Specification requirements for SJ & SL

**Typical Characteristics**

**ITASCA Lawnmower &  
Utility 4-Cycle 10W-30**

SAE Viscosity Grade	10W-30
Specific Gravity @ 60°F	0.8811
Gravity, °API	29.11
Flash Point, COC, °F	420
Pour Point Deg. F	-30
Viscosity (typical)	
@40 Deg. C, cSt	76.3
@100 Deg. C, cSt	11.2
Viscosity Index	135
Sulfated Ash, Wt. %	0.8
Zinc, Wt. %	0.10
Phosphorus, Wt. %, Max.	0.09
API Performance	SL

***Warren Oil Company, Inc.***

*Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:  
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72303*