



## Product Data Sheet

### Itasca Marine #2 Lithium Grease

Date Issued: July 24, 2008  
Date Revised: March 19, 2002

#### Typical Properties

NLGI Grade	NLGI	No. 2
Color	Match Std.	Blue
Penetration, W/60	ASTM D-217	265-295
Dropping Point; C (F)	ASTM D-2265	192 (378)
Timken OK Load (min)	ASTM D-2509	50 lbs.
Oil Separation	ASTM D-6184	< 3
Rust Test	ASTM D-1743	Pass
Roll Stability; 165rpm, 2hrs, 25C	ASTM D-1831	249
Change, pen	ASTM D-1831	+4
Change, %	ASTM D-1831	+1.6 %
Water Washout 175°F	ASTM D-1264	3.8 %
Water Washout 100°F	ASTM D-1264	2.2 %
Water Spray-off	ASTM D-4049	14.0 %
Four Ball EP:		
LNSL, klg	ASTM D-2596	100
Weld Point, kg	ASTM D-2596	315
LWI	ASTM D-2596	54.3
Four Ball Wear; scar dia., mm	ASTM D-2266	0.6 mm

Corporate Headquarters: 1440 Erie St., PO Box 12337, North Kansas City, MO 64116 Fax: 816-471-2240 Phone: 816-471-4590  
Manufacturing Facilities: 1437 Gentry St. North Kansas City, MO 64116 Fax: 816-471-7448 Phone: 816-471-4590  
150 Crutcher Rd. PO Box 308 Rosedale, MS 38769 Fax: 662-759-3674 Phone: 662-759-6808

The name of this product or group of products is for production identifications purposes only. Jesco makes no warranties, representation or conditions of any kind express or implied, whether of merchantability or fitness for use with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. Jesco sales personnel are not authorized to amend this warranty limitation.

November 30, 2006 Rev 3