



Coastal[®] Air-Cooled 2-Cycle Oil

COASTAL AIR-COOLED 2-CYCLE OIL is specially formulated for use in light-duty air-cooled 2-cycle engines under 40 HP. Contains anti-scuffing compounds for extra protection.

FOLLOW MANUFACTURER'S RECOMMENDED MIX: For 16-to-1 proportions mix 8 oz. with one gallon of gasoline. For 32-to-1 proportions mix 8 oz. with two gallons of gasoline. For 50-to-1 proportions mix one 6.4 oz. container with 2.5 gallons of gasoline. To mix, partially fill clean can with gasoline and add correct amount of **COASTAL AIR-COOLED 2-CYCLE OIL**. Shake well, then add remainder of gasoline to achieve proper proportion.

Typical Characteristics

	METHOD	TYPICAL
Viscosity 100°F, SUS	D445	380
Viscosity 210°F, SUS	D445	57
Viscosity 100°C, cSt	D445	9.40
Viscosity 40°C, cSt	D445	61.0
Viscosity Index	D2270	116
API Gravity @ 60°	D287	29.1
Specific Gravity @ 60°F	D1298	0.8811
Pounds per Gallon @ 60°F	D1250	7.337
Flash Point COC, °F (°C)	D92	195 (91)
Pour Point, °F (°C)	D97	-10(-23.3)
Finished Product Color		Blue



Warren Oil Company, LLC

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
 Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301