



Full Synthetic Tractor Hydraulic Fluid

COASTAL FULL SYNTHETIC TRACTOR HYDRAULIC FLUID is a universal low viscosity product formulated to lubricate transmissions, differentials and final drive gears at very low temperatures. The outstanding low temperature performance is provided by the use of full synthetic base oils and extremely shear stable viscosity index improvers. The additive package provides excellent friction control, oxidation resistance, wear protection, rust and corrosion inhibition, and resistance to foaming.

COASTAL FULL SYNTHETIC TRACTOR HYDRAULIC FLUID is specifically designed for use in applications calling for JDM **J20D** specification.

Benefits:

- Specially formulated for low temperature performance
- High viscosity index and shear stability
- Excellent anti-wear and extreme pressure properties
- Outstanding wet brake and chatter control
- Advanced rust and oxidation control



Warren Oil Company, LLC

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301



Full Synthetic Tractor Hydraulic Fluid

Typical Characteristics

Gravity, °API	35.6
Specific Gravity @ 60°F	0.847
Density, lb/gal	7.05
Flash Point °F	405
Pour Point °F	-55
Viscosity	
@ 40 °C, cSt	33.3
@ 100 °C, cSt	7.4
Viscosity Index	200
Viscosity, Brookfield	
cP @ -40°C	17,350
Product Code #	
Bulk	99000
Drum, 55 GAL	87155
Pail, 5 GAL	87105



Warren Oil Company, LLC

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301